



# INSTALLATION

## SMALL HALOGEN UNIVERSAL SILVER BULLETS 2305

**FITS: UNIVERSAL APPLICATIONS, SINGLE CIRCUIT, 20 WATT HALOGEN BULBS**

### PARTS INCLUDED

- 2 Small Halogen Silver Bullets (Light Bodies Tapped 3/8"–16, Hidden Wiring)
- 2 3/8"–16 x 1-1/2" Hollow Hex Bolts
- 2 3/8" I.D. Internal Tooth Lock Washers
- 1 Anti-Seize
- 1 Installation Instructions

*Please read and understand entire instructions before starting installation.*

### THANK YOU FOR CHOOSING KÜRYAKYN!

**IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND ATTENTION NOTES REGARDING THE USE AND CARE OF THIS PRODUCT.**

**ATTENTION!** This indication alerts you to the fact that ignoring the contents described herein may negatively affect product performance and functionality.

### ITEMS RECOMMENDED FOR INSTALLATION

- Test Light
- Service Manual

**ATTENTION!** Be sure to use the supplied anti-seize on all threaded fasteners before installation. This will reduce galling and make future removal of the fasteners easier.

### NOTES

Silver Bullets are not D.O.T. approved and are intended for use as auxiliary running, turn, or brake lights only.

Universal Silver Bullets can be installed just about anywhere. Kuryakyn's P-clamps and Two-Piece Fork Mounts work great to attach Silver Bullets to engine guards, frame tubes, or fork tubes.

The Hidden Wiring Kits include bolts that are 1-1/2" long. On some applications these long bolts may contact the bulb or plug inside the light casing before the they can be tightened completely. If you encounter this situation, simply shorten the bolt using a hack-saw or "cut-off" tool.

### PROCEDURE FOR SINGLE CIRCUIT HALOGEN DRIVING WIRING

The black wire from the Silver Bullet is the power wire. The ground is the Silver Bullet Housing.

**-cont.-**

### CUSTOMER SERVICE

877.370.3604 (toll free)

### INSTALLATION QUESTIONS

techsupport@kuryakyn.com  
or call 715.247.2983

### LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
- The product must be properly installed, maintained and operated under normal conditions.
- Kuryakyn makes no warranty, expressed or implied, with respect to any gold plated products.
- Kuryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in non-conforming condition, or for any breach of contract or duty between Kuryakyn and a customer.
- Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
- Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. Components of Kuryakyn products containing L.E.D.s will be warranted for defects in materials and workmanship for 3 years from the date of purchase.
- Kuryakyn makes no warranty of any kind in regard to other manufacturer's products distributed by Kuryakyn. Kuryakyn will pass on all warranties made by the manufacturer and where possible, will expedite the claim on behalf of the customer, but ultimately, responsibility for disposition of the warranty claim lies with the manufacturer.

### ABOUT OUR CATALOG

You'll find all our innovations for H-D, GL and Metric Cruisers in our annual catalogs. Order online today—select the "CATALOGS" icon. Each Kuryakyn® product comes with a Proof-of-Purchase good for a complimentary catalog. Details in packaging.

Be sure to ask your local dealer about other Kuryakyn products, the motorcycle parts and accessories designed for riders by riders.

©2005 Kuryakyn USA® All Rights reserved.



kuryakyn.com

**SILVER BULLET WIRING:**

Black Wire — Power (Hot)

Silver Bullet Housing — Ground

Wiring and accessory circuits are protected by a 10 or 15 amp circuit. Adding these lights will place an approximate additional 4 amp draw on this circuit. This additional load may be too much amperage on that circuit and may cause a circuit breaker to trip, or blow a fuse. You may want to wire these to an accessory circuit or use a relay kit, Küryakyn P/N 2328.

**IMPORTANT**

Once these lights have been installed and wired, seal the wire passage of the hollow bolts with silicone to prevent water from entering the Silver Bullet Housing.

*Ride On!*

**Küryakyn®**

PAGE

**2**